


SAFETYDATASHEET

1. Product and Company Identification

Product identifier	W SERIES SOLVENT BASED STAINS – NON REGULATED
Other means of identification	0113, W200, W201, W210, W215, W218, W231, W233, W234, W235, W236, W238, W239, W240, W242, W243, W246, W247, W248, W249, W250, W251, W252, W253, W254, W255, W256, W354, W355, WS200482, WS201020, WS201520, WS201811
Recommended use	
Recommended restrictions	
Manufacturer information	Fast Dry Pigmented Wiping Stains None known. John E. Goudey Manufacturing Limited 21 Primrose Avenue Toronto, ON M6H 3V1 CA Phone: (416)531-4669
Supplier	See above.
CANUTEC	(613) 996-6666

2. Hazards Identification

Physical hazards	Flammable liquids	Label elements	
Health hazards	Skin corrosion/irritation Serious eye damage/eye irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity, single exposure Specific target organ toxicity, single exposure Specific target organ toxicity, repeated exposure Aspiration hazard	Category 4 Category 2 Category 2 Category 2 Category 2	
Environmental hazards	Not classified.		
WHMIS 2015 defined hazards	Not classified		
Signal word	Danger		
Hazard statement	Combustible liquid. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation.		

Category 3 respiratory tract irritation
Category 3 narcotic effects
Category 1 (central nervous system)

None known.

Category 1

May cause drowsiness or dizziness. Causes damage to organs (central nervous system exposure). May be fatal if swallowed and enters

Precautionary statement Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Prevention Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist or vapor. Use only outdoors or in a wellventilated area. Do not eat, drink or smoke when using this product.

Response

In case of fire: Use appropriate media to extinguish. IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned:

Storage

Disposal

WHMIS 2015: Health Hazard(s) otherwise classified (HHNOC)

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) Hazard(s) not otherwise classified (HNOC) Supplemental information Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known **not**

None known

None.

3. Composition/Information on Ingredients

4. First Aid Measures

CENTER or doctor/physician if you feel unwell.

Skin contact

attention and special treatment needed

Eye contact

IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Ingestion

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects. Treat patient symptomatically.

Indication of immediate medical

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON

Mixture

Chemical name	Common name and synonyms	CAS number	%	
Benzene, ethyl-		100-41-4	1-5*	solvent
Carbon black		1333-86-4	0.1-1*	8052-
Ferric oxide		1309-37-1	1-5*	
Heavy aromatic solvent naphtha (petroleum)		64742-94-5	45-70*	Xylene 1330-
Hydrous magnesium silicate		14807-96-6	0.1-1*	All
Naphtha (petroleum), heavy alkylate		64741-65-7	0.1-1*	
Silica, amorphous, fumed, crystalline free		112945-52-5	0.1-1*	
Solvent naphtha (petroleum), medium aliphatic		64742-88-7	1-5*	

concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical mixtures The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

Hazardous combustion products May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Never return spills to original containers for re-use. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
	TW	543 mg/m3	
	A	125 ppm	
		434 mg/m3	
	TW	100 ppm	
	A	Repirabl	
		3.5 e. mg/m3	
		5 mg/m3	
Benzene, ethyl- (CAS 100-41-4)	STEL	3 e particles.	
		2 mg/m3	
Carbon black (CAS 1333-86-4)		3	
Ferric oxide (CAS 1309-37-1)		1590	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	Type	
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	3 mg/m3	
		Value	
			Form

Components	Type	Value	Form
Stoddard solvent (CAS 8052-41-3)	TWA	400 ppm	
		572 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	
Ferric oxide (CAS 1309-37-1)	STEL	10 mg/m3	Inhalable Fume.

	TWA	5 mg/m ³	Fume.	fraction.
		5 mg/m ³	Dust.	
		3 mg/m ³	Respirable	
		10 mg/m ³	Total dust.	
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	200 mg/m ³	Non-aerosol.	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m ³	Non-aerosol.	
Stoddard solvent (CAS 8052-41-3)	STEL	580 mg/m ³		
	TWA	290 mg/m ³		
	STEL	150 ppm		
Xylene (CAS 1330-20-7)	TWA	100 ppm		

Canada. Manitoba OELs (Reg. 217/2006, Th

		Type	Value	Form
Benzene, ethyl- (CAS 10041-4)	TWA TWA		20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)				
Ferric oxide (CAS 1309-37-1)	TWA		3 mg/m ³	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA		5 mg/m ³	Non-aerosol.
			200 mg/m ³	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA			Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA		2 mg/m ³	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)			200 mg/m ³	
Xylene (CAS 1330-20-7)	TWA			
	STEL		100 ppm	
	TWA		150 ppm	
			100 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents

Components	Type	Value	Form
Benzene, ethyl- (CAS 10041-4)	TWA	20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)			Respirable fraction.
Ferric oxide (CAS 1309-37-1)	TWA	3 mg/m ³	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	5 mg/m ³	
	TWA	2 fibers/ml	

		2 mg/m3	Respirable fraction.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)		525 mg/m3	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	TWA	150 ppm	
	STEL TWA	100 ppm	
Canada. Quebec OELs. (Ministry of Labor Regulation Respecting the Quality of the Work Environment) Form			
Components	Type	Enviro Value	Form
Benzene, ethyl- (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3	
		100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	
	TWA	10 mg/m3	Dust and fume.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)		1590 mg/m3	Total dust.
		400 ppm	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable dust.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	1590 mg/m3	
		400 ppm	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	1590 mg/m3	
		400 ppm	
Stoddard solvent (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3	
		150 ppm	
	TWA	434 mg/m3	
		100 ppm	
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Type	Value	Form

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	PEL	400 mg/m3
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	PEL	100 ppm 400 mg/m3
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	PEL	100 ppm 400 mg/m3
Stoddard solvent (CAS 8052-41-3)	PEL	100 ppm 2900 mg/m3
Xylene (CAS 1330-20-7)	PEL	500 ppm 435 mg/m3 100 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable
		15 mg/m3	Total dust
		50 mppcf	Total dust
		15 mppcf	Respirable
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable
	TWA	2.4 mppcf	Respirable.
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)		0.8 mg/m3	
		20 mppcf	

**US. ACGIH Threshold Limit Values
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
Benzene, ethyl- (CAS 10041-4)	TWA TWA	20 ppm	Inhalable fraction.
Carbon black (CAS 133386-4)			
Ferric oxide (CAS 1309-37-1)	TWA	3 mg/m3	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	5 mg/m3	Non-aerosol.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	200 mg/m3	Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	2 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	200 mg/m3	
Xylene (CAS 1330-20-7)	STEL	100 ppm	
	TWA	150 ppm	
		100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards
Components**

<u>Components</u>	<u>Type</u>	<u>Value</u>	<u>Form</u>
-------------------	-------------	--------------	-------------

Benzene, ethyl- (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
Carbon black (CAS 1333-86-4)	TWA	0.1 mg/m3

US. NIOSH: Pocket Guide to Chemical Haz Components	ards Type	Value	Form
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	400 mg/m3	
		100 ppm	
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	TWA	6 mg/m3	
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Xylene (CAS 1330-20-7)	STEL TWA	655 mg/m3	
		150 ppm	
		435 mg/m3	
		100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen Sampling Time
Benzene, ethyl- (CAS 100-41-4)	0.15 g/g	Sum of Creatinine * mandelic acid in urine and phenylglyoxylic acid	
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric Creatinine * acids in urine	

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) Can be absorbed through the skin.

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) Can be absorbed through the skin.

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Canada - Manitoba OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Canada - Ontario OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Canada - Saskatchewan OELs: Skin designation Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

US ACGIH Threshold Limit Values: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Can be absorbed through the skin.

Appropriate engineering Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates **controls** should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. **Individual protection measures, such as personal protective equipment**

Upper/lower flammability or explosive limits

Eye/face protection	As required by employer code.
Skin protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
Hand protection	Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). Not applicable.
Other	
Respiratory protection	
Thermal hazards	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

General hygiene considerations

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form Color	Colored
Odor Odor threshold pH	Aromatic.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	< 32 °F (< 0 °C)
Pour point	181.4 - 354.2 °F (83 - 179 °C)
Specific gravity	
Partition coefficient (n-octanol/water)	Not available.
Flash point	0.95 - 1.05
Evaporation rate	Not available.
Flammability (solid, gas)	149.0 °F (65.0 °C) TCC
Wear safety glasses with side shields (or goggles).	Not available.
	Not applicable.

Impervious gloves. Confirm with reputable supplier first.

Flammability limit - lower (%)

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%) Not available. **Explosive**

limit - upper (%) Vapor pressure Vapor density

Relative density Solubility(ies) Not available. **Auto-ignition temperature** Not available.

Decomposition temperature 5.5 mm Hg @20C

Viscosity N

Other information Explosive properties Oxidizing o

properties t

VOC (Weight %) a

v

a

i

10. Stability and Reactivity

Reactivity

This product may react with strong oxidizing agents.

1 a

b ol ne d
 .
 N oo nt aa Zv aa hi nl s
 #a 2b
 l Ne o
 . t
 N ee x
 g pl li og si i
 b vl e
 . e
 N
 Not available. o
 N
 ot t
 o
 ax
 v i
 aid
 la i bl ze. i
 1 n
 6 gs .
 e 716 - 788 g/l c

Incompatible materials
Hazardous decomposition products

Material is stable under normal conditions.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals.

Strong acids. Strong oxidizing agents. Halogens. Aluminum. Strong bases. May include and are not limited to: Oxides of carbon.

Routes of exposure

Information on likely routes of

Ingestion

Inhalation

Skin contact

Eye contact

Symptoms related to the physical, chemical and toxicological characteristics Hazardous polymerization does not occur.

11. Toxicological Information

Eye, Skin contact, Inhalation, Ingestion. **posure**

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.

Causes skin irritation.

Causes serious eye irritation.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

Components

Benzene, ethyl- (CAS 100-41-4)

Acute

Dermal LD50

Ferric oxide (CAS 1309-37-1) **Acute**

Dermal LD50

Inhalation

LC50

May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Inhalation
LC50

Oral
LD50

Species

Rabbit

Test Results

17800 mg/kg, HSDB
 15380 mg/kg, CCOHS: Cheminfo
 17.8 ml/kg, 24 Hours, ECHA

Carbon black (CAS 1333-86-4)

Acute

Dermal LD50

Inhalation
LC50

Oral
LD50

Mouse

Rat

Rat

> 8000 ppm, 20 Minutes, ECHA
 4000 ppm, 4 Hours, CCOHS: Cheminfo

5460 mg/kg, HSDB
 3500 mg/kg, Sigma Aldrich
 5.5 g/kg, ECHA/HSDB

> 8000 mg/kg, ECHA/HSDB

Rabbit > 3000 mg/kg

Not available

Rat > 15400 mg/kg
>

1
Not available
0

#28351

Components	Species	Test Results
<i>Oral</i>		
LD50	Rat	> 10000 mg/kg, ECHA
aromatic solvent naphtha (petroleum) (CAS 64742-94-5)		> 5000 mg/kg, ECHA Heavy
Acute		
<i>Dermal</i>		
LD50 Rabbit		> 6000 mg/kg, 24 Hours
		> 4000 mg/kg, 24 Hours
		> 2000 mg/kg, 24 Hours, ECHA
	Rat	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50 Rat		> 7.5 mg/L, 6 Hours, ECHA
		> 4.3 mg/L, 4 Hours, ECHA
		> 0.1 mg/L, 8 Hours, ECHA <i>Oral</i>
LD50	Rat	> 5000 mg/kg
		> 2000 mg/kg, ECHA
		7050 mg/kg, HMIRC
		5800 mg/kg, ECHA
		4820 mg/kg, ECHA Hydrus
magnesium silicate (CAS 14807-96-6)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, ECHA
<i>Inhalation</i>		> 2.1 mg/L, 4 h, ECHA
	LC50 Rat	
<i>Oral</i>		> 5000 mg/kg, ECHA
LD50	Rat	
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)		
Acute		
<i>Dermal</i>		
LD50 Rabbit		> 6000 mg/kg, 24 Hours, ECHA
		> 3750 mg/kg, 24 Hours, ECHA
		> 3000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, ECHA

Components

Species Test Results

> 2000 mg/kg, 24 Hours,
ECHA

> 1900 mg/kg, 24 Hours,

ECHA *Inhalation*

LC50 Rat > 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA

> 7630 mg/m3, 4 Hours, ECHA

> 7300 mg/m3, 4 Hours, ECHA

> 5830 mg/m3, 4 Hours, ECHA

> 5740 mg/m3, 4 Hours, ECHA

> 5610 mg/m3, 4 Hours, ECHA

> 5470 mg/m3, 4 Hours, ECHA

> 5300 mg/m3, 4 Hours, ECHA

> 5280 mg/m3, 4 Hours, ECHA

> 5260 mg/m3, 4 Hours, ECHA

> 5250 mg/m3, 4 Hours, ECHA

> 5240 mg/m3, 4 Hours, ECHA

> 5220 mg/m3, 4 Hours, ECHA

Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)

Acute

Dermal

LD50

Rabbit

Inhalation LC50 Rat

Components

Species Test Results

>
5570

> 5200 mg/m3, 4 Hours, ECHA

> 5170 mg/m3, 4 Hours, ECHA

> 5160 mg/m3, 4 Hours, ECHA

> 5100 mg/m3, 4 Hours, ECHA

> 5080 mg/m3, 4 Hours, ECHA

> 5050 mg/m3, 4 Hours, ECHA

Oral
LD50

Rat
mg/kg, ECHA > 4800 mg/kg, ECHA > 5200 mg/kg, ECHA
> 4500 mg/kg, ECHA > 5000 mg/kg, ECHA

> 5040 mg/m3, 4 Hours, ECHA
> 5020 mg/m3, 4 Hours, ECHA
> 5000 mg/m3, 4 Hours, ECHA
> 4980 mg/m3, 4 Hours, ECHA
> 4970 mg/m3, 4 Hours, ECHA
> 4420 mg/m3, 4 Hours, ECHA
> 5.4 mg/L, 4 Hours, ECHA
> 5.1 mg/L, 4 Hours, ECHA
> 5.1 mg/L, 4 Hours, ECHA
> 5 mg/L, 4 Hours, ECHA
> 5 mg/L, 4 Hours, ECHA
73680 mg/L, 4 Hours, HSDB
>= 5060 mg/m3, 4 Hours, ECHA
61 mg/L, 4 Hours, HSDB
> 7000 mg/kg, ECHA
> 6000 mg/kg, ECHA
> 25 ml/kg, HSDB
14063 mg/kg, ECHA

Components

Species Test Results

		6620 mg/kg, ECHA
		5800 mg/kg, ECHA
		5390 mg/kg, ECHA
		4820 mg/kg, ECHA
		> 5000 mg/kg, 24 Hours, ECHA
		> 2000 mg/kg, 24 Hours
		> 58.8 mg/L, 4 Hours, ECHA
		> 2.1 mg/L, 4 Hours, ECHA
		> 0.7 mg/L, 4 Hours, ECHA
		> 0.1 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Mouse	> 15000 mg/kg, HSDB
		> 3160 mg/kg
	Rat	> 10000 mg/kg, ECHA
		> 5000 mg/kg, ECHA
		> 3300 mg/kg
		3160 mg/kg, LOLI
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)		
Acute Dermal		
LD50	Rabbit	> 4000 mg/kg, 24 Hours
		> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
		3000 mg/kg, NIOSH
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/L, 6 Hours
	Rat	> 7.5 mg/L, 6 Hours
		> 6 mg/L, 4 Hours, ECHA

Components

Species Test Results

			> 5.7 mg/L, 4 Hours, ECHA
			> 5.3 mg/L, 4 Hours, ECHA
			> 5.3 mg/L, 4 Hours, ECHA
			> 5.2 mg/L, 4 Hours, ECHA
			> 4.6 mg/L, 4 Hours, ECHA
			> 4.5 mg/L, 4 Hours, ECHA
			> 4.3 mg/L, 4 Hours
			> 0.1 mg/L, 8 Hours
			5.3 mg/l/4h, NIOSH
<i>Oral</i>			
LD50	Rat		> 20000 mg/kg
			> 5000 mg/kg, NIOSH
			> 25 ml/kg
Stoddard solvent (CAS 8052-41-3)			
Acute			
<i>Dermal</i>			
LD50	Rabbit		> 3000 mg/kg
<i>Inhalation</i>			
LC50	Rat		> 5500 mg/m3
<i>Oral</i>			
LD50	Rat		> 5000 mg/kg
Xylene (CAS 1330-20-7)			
Acute			
<i>Dermal</i>			
LD50	Rabbit		> 5000 ml/kg, 4 Hours, ECHA
			> 43 g/kg, HSDB
			12126 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>			
LC50	Mouse		3907 mg/L, 6 Hours, HSDB
			3907 ppm, 6 Hours, HSDB
	Rat		6700 ppm, 4 Hours, ECHA

Components

Species Test Results

Oral
LD50

Skin corrosion/irritation

Exposure minutes

Erythema value

Oedema value

**Serious eye damage/eye
irritation**

Corneal opacity value

Iris lesion value

Conjunctival reddening value Conjunctival oedema value

Recover days

Respiratory or skin sensitization

Respiratory sensitization

Components

Species Test Results

Skin sensitization

HA/HSDB

Mutagenicity

6247 ppm, 4 Hours, ECHA

Carcinogenicity

ACGIH Carcinogens

5922 ppm, 4 Hours, ECHA

5627 mg/kg, ECHA/HSDB

6

5251 mg/kg, ECHA

5

8

0

> 4000 mg/kg, ECHA 6670

p

mg/kg, HSDB

p

m

4300 mg/kg, ECHA/HSDB

Mouse

,

4

3523 mg/kg

H

o

u

10 ml/kg, ECHA

Rat

r s

Causes skin irritation. ,

E Not available.

C

Not available.

H

Not available.

A

Causes serious eye irritation.

6 3

Not available.

5

Not available.

0

Not available.

p p

m

Not available.

,

Not available.

4

H

o

Not a respiratory sensitizer. u

This product is not expected to cause skin sensitization. r

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. '

E

Suspected of causing cancer. See below. C

Benzene, ethyl- (CAS 100-41-4)

Carbon black (CAS 1333-86-4)

Crystalline silica (CAS 14808-60-7) Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Canada - Alberta OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7)

Canada - Manitoba OELs: carcinogenicity

CARBON BLACK, INHALABLE FRACTION (CAS 1333-86-4)

ETHYL BENZENE (CAS 100-41-4)

KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-88-7)
KEROSENE (NON-AEROSOL), AS TOTAL

HYDROCARBON VAPOR (CAS 64742-94-5) SILICA, CRYSTALLINE-.ALPHA.-QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7) **Canada -**

Quebec OELs: Carcinogen category

Crystalline silica (CAS 14808-60-7)

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzene, ethyl- (CAS 100-41-4) Carbon black (CAS 1333-86-4) Crystalline silica (CAS 14808-60-7) A3 Confirmed animal carcinogen with unknown relevance to humans.

A3 Confirmed animal carcinogen with unknown relevance to humans.

A2 Suspected human carcinogen.

A3 Confirmed animal carcinogen with unknown relevance to humans.

A3 Confirmed animal carcinogen with unknown relevance to humans.

Suspected human carcinogen.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Confirmed animal carcinogen with unknown relevance to humans.

Suspected human carcinogen.

Suspected carcinogenic effect in humans.

Volume 77 - 2B Possibly carcinogenic to humans.

Volume 65, Volume 93 - 2B Possibly carcinogenic to humans. Volume 68, Volume 100C 1 Carcinogenic to humans.

Ferric oxide (CAS 1309-37-1)

Volume 1, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.

Hydrous magnesium silicate (CAS 14807-96-6)

Volume 42, Supplement 7, Volume 93 - 3 Not classifiable as to carcinogenicity to humans.

Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)

Volume 93 - 2B Possibly carcinogenic to humans.

Stoddard solvent (CAS 8052-41-3)

Volume 68 - 3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

Volume 47 - 3 Not classifiable as to carcinogenicity to humans.

Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene, ethyl- (CAS 100-41-4)

Carbon black (CAS 1333-86-4)

Crystalline silica (CAS 14808-60-7)

US NTP Report on Carcinogens: Known carcinogen

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen. **US. OSHA Specifically**

Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7)

Cancer

Reproductive toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)

Algae

IC50

Alg

Algae

IC50

Algae

Aquatic

Crustacea	EC50	Daphnia	Crustacea	EC50	W
Aquatic			Fish	LC50	Ra
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.5 mg/L, 72 Hours		(O
			0.95 mg/L, 48 Hours		
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)			8.8 mg/L, 96 hours		

#28351

Page: 21 of 27

Issue date 27-June-2018

Teratogenicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Xylene is considered fetotoxic in humans, based on observations of reduced fetal weight, delayed ossification and persistent behavioural effects in animal studies in the absence of maternal toxicity.

Specific target organ toxicity - May cause respiratory irritation. May cause drowsiness and dizziness. single exposure

Specific target organ toxicity - Causes damage to organs (central nervous system) through prolonged or repeated exposure. repeated exposure Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Significant lung effects have been observed in animals following exposure to airborne concentrations of Carbon Black of less than 100 mg/m3.

12. Ecological Information

Ecotoxicity Ecotoxicological data	See below Components	Species	Test Results
Benzene, ethyl- (CAS 100-41-4) IC50		Algae	4.6 mg/L, 72 Hours
Algae			
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours
Aquatic	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/L, 48 hours
Crustacea		Fish LC50 Fathead minnow (Pimephales)	
promelas) 7.5 - 11 mg/L, 96 hours			

8.8 mg/L, 96 hours

30000 mg/L, 72 Hours

LC50

Fish
(Oncorhynchus mykiss)

2.7 - 5.1 mg/L, 48 hours

Components

Species

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)

Xylene (CAS 1330-20-7)

Crustacea

EC50

Daphnia

Aquatic

Aquatic

EC50

Water flea (Daphnia pulex)

Fish

LC50

Bluegill

(Lepomis macrochirus)

Crustacea

8.8 mg/L, 96 hours

2.7 - 5.1 mg/L, 48 hours

8.8 mg/L, 96 hours

8.8 mg/L, 96 hours

8.8 mg/L, 96 hours

Test Results

100 mg/L, 48 Hours

7.711 - 9.591 mg/L, 96 hours

Persistence and degradability
Bioaccumulative potential

No data is available on the degradability of this product.

Mobility in soil

No data available.

Mobility in general

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Hazardous waste code	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Waste from residues / unused products	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Contaminated packaging	

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
---	--

General

Canada: Marine Pollutants Exemption. 1.45.1. : Part 3, Documentation, and Part 4, Dangerous Goods Safety Marks, do not apply to substances that are classified as marine pollutants in accordance with section 2.43 of Part 2, Classification, if they are in transport solely on land by road vehicle or railway vehicle. However, substances may be identified as marine pollutants on a shipping document and the required dangerous goods safety marks may be displayed when they are in transport by road or railway vehicle. (SOR/2008-34, s. 23)

US: DOT - 49 CFR 173.150 (f) - Combustible Liquid Exemption

CFR 171.4: The requirements of this subchapter specific to marine pollutants does not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft, except when all or part of the transportation is by vessel.

#28351

Page: 22 of 27

Issue date 27-June-2018

U.S. Department of Transportation (DOT) Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada) Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations contains all the information req d in accordance with the hazard criteria of the HPR and the SDS uired by the HPR. **Canada CEPA Schedule I: Listed substance** 2-Butanone, oxime (CAS 96-29-7) Listed. Ferric oxide (CAS 1309-37-1) Listed.

Hydrous magnesium silicate (CAS 14807-96-6) Listed. **Canada**

DSL Challenge Substances: Listed substance

2-Butanone, oxime (CAS 96-29-7) Listed. Carbon black (CAS 1333-86-4)

Listed. Crystalline silica (CAS 14808-60-7) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	1 TONNES
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	1 TONNES
Stoddard solvent (CAS 8052-41-3)	1 TONNES
Xylene (CAS 1330-20-7)	1 TONNES

Canada Priority Substances List (Second List): Listed substance

Ferric oxide (CAS 1309-37-1) Listed.

Hydrous magnesium silicate (CAS 14807-96-6) Listed. **Export Control**

List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene, ethyl- (CAS 100-41-4) Listed. Manganese Oxide (CAS 1317-34-6)
Listed. Xylene (CAS 1330-20-7) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Crystalline silica
(CAS 14808-60-7) Cancer

lung effects immune
system effects kidney effects

Benzene, ethyl- (CAS 100-41-4)

Listed. **Superfund Amendments and Reauthorization Act of**

1986 Carbon black (CAS 1333-86-4) Listed. **(SARA)** Ferric oxide (CAS 1309-37-1)
Listed.

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-Listed.
94-5)

Hydrous magnesium silicate (CAS 14807-96-6) Listed.

Manganese Oxide (CAS 1317-34-6) Listed. Naphtha (petroleum),
heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous,
fumed, crystalline free (CAS 112945- Listed. 52-5)

#28351

Page: 23 of 27

Issue date 27-June-2018

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No
No

SARA 302

No

Extremely hazardous substance

SARA

311/312

Hazardous

chemical

%

SARA 313 (TRI CAS by reporting) number wt.

Chemical name

100-41- 1-

Benzene, 4 5* ethyl- 1330- 10Xylene 20-7 30*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Benzene, ethyl- (CAS 100-41-4)
Manganese Oxide (CAS 1317-34-6)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.
Stoddard solvent (CAS 8052-41-3) Listed.
Xylene (CAS 1330-20-7) Listed.

US - Illinois Chemical Safety Act: Listed substance

Benzene, ethyl- (CAS 100-41-4)
Manganese Oxide (CAS 1317-34-6)
Xylene (CAS 1330-20-7)

US - Louisiana Spill Reporting: Listed substance

Benzene, ethyl- (CAS 100-41-4) Listed.
Manganese Oxide (CAS 1317-34-6) Listed.
Xylene (CAS 1330-20-7) Listed.

US - Michigan Critical Materials Register: Parameter number

Xylene (CAS 1330-20-7) XYLENE (ALL ISOMERS)

US - Minnesota Haz Subs: Listed substance

2-Butanone, oxime (CAS 96-29-7) Listed. Benzene, ethyl- (CAS 100-41-4) Listed. Carbon black (CAS 1333-86-4) Listed. Crystalline silica (CAS 14808-60-7) Ferric Listed. oxide (CAS 1309-37-1) Listed.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742- Listed. 94-5)
Hydrous magnesium silicate (CAS 14807-96-6) Listed. Manganese Oxide (CAS 1317-34-6) Listed.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous, fumed, crystalline free (CAS 11294552-5) Listed.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.
Stoddard solvent (CAS 8052-41-3) Listed. Xylene (CAS 1330-20-7) Listed.

US - New Jersey RTK - Substances: Listed substance

Benzene, ethyl- (CAS 100-41-4)
Carbon black (CAS 1333-86-4)
Crystalline silica (CAS 14808-60-7)
Ferric oxide (CAS 1309-37-1)
Hydrous magnesium silicate (CAS 14807-96-6)
Manganese Oxide (CAS 1317-34-6)
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
Stoddard solvent (CAS 8052-41-3)
Xylene (CAS 1330-20-7)

US - North Carolina Toxic Air Pollutants: Listed substance

Manganese Oxide (CAS 1317-34-6)
Xylene (CAS 1330-20-7)

US - Texas Effects Screening Levels: Listed substance

2-Butanone, oxime (CAS 96-29-7) Listed. Benzene, ethyl- (CAS 100-414) Listed. Carbon black (CAS 1333-86-4) Listed. Crystalline silica (CAS 14808-60-7) Listed. Ferric oxide (CAS 1309-37-1) Listed.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742- Listed. 94-5)
Hydrous magnesium silicate (CAS 14807-96-6) Listed. Manganese Oxide (CAS 1317-34-6) Listed.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed. Silica, amorphous, fumed, crystalline free (CAS 11294552-5) Listed.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Listed.
Stoddard solvent (CAS 8052-41-3) Listed. Xylene (CAS 1330-20-7) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Benzene, ethyl- (CAS 100-41-4)

US. Massachusetts RTK - Substance List

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
- Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)
- Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

- Benzene, ethyl- (CAS 100-41-4)
- Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)
- Manganese Oxide (CAS 1317-34-6)
- Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Manganese Oxide (CAS 1317-34-6)
- Silica, amorphous, fumed, crystalline free (CAS 112945-52-5) Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

US. Rhode Island RTK

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)
- Ferric oxide (CAS 1309-37-1)
- Hydrous magnesium silicate (CAS 14807-96-6)
- Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
- Stoddard solvent (CAS 8052-41-3)
- Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

- Benzene, ethyl- (CAS 100-41-4) Listed: June 11, 2004
- Carbon black (CAS 1333-86-4) Listed: February 21, 2003
- Crystalline silica (CAS 14808-607) Listed: October 1, 1988

Inventory status


Country(s) or region	Inventory name	On inventory	Canada	Domestic Substances List (DSL)	(yes/no)*	
Canada	Non-Domestic Substances List (NDSL)					Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory					No
						Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

27-June-2018

Version #

03

Effective date

27-June-2018

Prepared by

Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.